

PRODUCT SHEET

Blynclight Mini

Blynclight Series

Status light with ringer designed for laptops and monitors.

Ideal for the open-plan workplace and call center.

Blynclight Mini



Key features

- Automatically displays User Presence/Status/Availability
- Designed for Laptops and Monitors – includes detachable mount for simple placement.
- Rings on Incoming Call and/or Instant Message
- Stepped Volume and Brightness Control
- Central management with Enterprise Admin Console
- Supports Microsoft Windows and Apple Mac operating systems
- Supports number UC/Softphone and Call Center applications including Skype for Business, Microsoft Lync, Cisco Jabber, RingCentral and Cisco Finesse.

Product Overview

The Blynclight Mini is a productivity tool designed to allow a user to control their availability in a workplace. The device will alert colleagues when a user is on a call, busy with an assigned task or available to collaborate. The device can also be configured to play ring and message tones on incoming calls and/or instant messages.

The Blynclight Mini automatically displays user presence/status by synchronizing with the users UC application (Skype for Business, Cisco Jabber, RingCentral etc.). As the users presence/status changes within the UC application so does the color of the Blynclight with the light color displayed matching that of users current presence/status.

By displaying user availability in this manner, a user can increase their productivity by limiting interruptions caused by colleagues in their work environment.

Features and benefits

Lighting

- **Display Surface**
Mini cube design with matte finish allows the light to effectively display user visual alerts yet remain unobtrusive.
- **Full RGB LED**
LED using the RGB color model allows any color to be displayed on the device.
- **Brightness Control**
10 step brightness control allows the light to be set in any environment without being distracting.

Audio

- **Built-in speaker**
Positioned within the device to ensure sound is clear and directed to the user.
- **Ring and Message tones**
Designed for the corporate environment, the device provides 14 different tones that can be configured to play on incoming call, instant message and/or status change.
- **Volume Control**
10 step volume control ensures the device can be set to an audible range without being distracting.

Connection

- **Micro-USB**
The device includes a 5ft grey USB cable which plugs into a female Micro-USB port on the device. The device has been designed to allow the USB cable to be interchangeable to allow for environments that require a longer or shorter cable.

Deployment

- **Enterprise Admin Console**
Management application that allows an administrator to develop a Blynclight configuration to be pushed out to all machines and prevent client machines from configuring their own devices.
- **Group Policy**
Blynclight Mini configurations can be deployed across an organisation using Group Policy to ensure all devices are configured in a consistent manner.

Warranty and support

- 12-month replacement warranty
Devices will be replaced if it has failed or found to have any malfunction within a 12 month period.
- Electronic and telephone support
Online support ticket system with telephone and remote control assistance for escalations.
- Software releases
The Blynlight application is continually being improved with regular software updates based on customer feedback.
- Developer forum
Join the Embrava Developer Forum to gain access to a host of applications built by our developer community geared towards the Blynlight.

Supported Platforms


Operating Systems

- Microsoft Windows - XP, Vista, 7, 8 (32-bit and 64-bit)
- Apple Mac OSX - 10.6, 10.7, 10.8, 10.9
 - Requires Lync Server 2013 for synchronized presence display.
 - Presence display only - does not support incoming call/instant message alerts.

Applications

- Skype for Business/Microsoft Lync 2013, 2010
- Skype for Windows Desktop v7
- Cisco Jabber for Windows 11, 10, 9
- RingCentral
- Cisco Finesse
- CounterPath Bria 4
- Google+ Hangouts (on-call alerts only)
- Lync Attendant 2010
 - Requires Lync Server 2013 for synchronized presence display.
 - Presence display only - does not support incoming call/instant message alerts.

Specifications

Physical Characteristics	
Dimensions	0.55(w) x 0.47(d) x 2.56(h) in. / 14(w) x 12(d) x 65(h) mm.
Weight	0.29oz / 8.28g
Interface	
Adapter	Micro-B receptacle
Protocol	Supports USB 1.1, 2.0, 3.0
Cable	Black 5ft Micro-B plug
Lighting	
LED	1 x RGB LED
Color	Supports full RGB color model
Brightness	10 step brightness adjustment
Sound	
Speaker	8Ω, Ø10mm
Tones	14 ring/message tones
Volume	10 step volume adjustment
Mounting	
	 <ul style="list-style-type: none"> • Plastic mount - slides into base of Blynclight Mini.. • 0.78(w) x 0.78(h) in. / 20(w) x 20(h) mm • 3M mount adhesive used to attach plastic mount to desired position.
Packaging	
	<ul style="list-style-type: none"> • Brown card box • 2.16(w) x 2.0(d) x 3.7(h) in. / 55(w) x 51(d) x 94(h) mm • 2.32oz / 65.9g • Includes Blynclight, USB cable, mount adhesive, instruction slip
Environment	
Operating temperature	14° to 122° F / -10° to 50° C
Heat emitted	< 32° F / < 0.1° C
Electrical Characteristics	
Maximum voltage	5 V
Maximum current	300 mA
Power rating	1.5 W
Compliance	
	<ul style="list-style-type: none"> • CE • RoHS

© Copyright 2017 Embrava Inc.

Skype, Lync and Windows are either registered trademarks of Microsoft Corporation in the United States and/or other countries.

Mac and OS X are trademarks of Apple Inc., registered in the U.S. and other countries.

Cisco Jabber is a trademark of Cisco Systems Inc., registered in the U.S. and other countries.

RingCentral is a trademark of RingCentral Inc., registered in the U.S. and other countries.

Google is a trademark of Google Inc., registered in the U.S. and other countries.

CounterPath is a trademark of CounterPath Corporation, registered in the U.S. and other countries.