



PRODUCT SHEET

Blynclight Plus

Blynclight Series

Status light with ringer that displays your presence/availability in the office.

Ideal for the open-plan workplace and call center.

Blynclight Plus



Key features

- Automatically displays User Presence/Status/Availability
- Rings on Incoming Call and/or Instant Message
- Stepped Volume and Brightness Control
- Central management with Enterprise Admin Console
- Supports Microsoft Windows and Apple Mac operating systems
- Supports number UC/Softphone and Call Center applications including Skype for Business, Microsoft Lync, Cisco Jabber, RingCentral and Cisco Finesse.

Product Overview

The Blynclight Plus is a productivity tool designed to allow a user to control their availability in a workplace. The device will alert colleagues when a user is on a call, busy with an assigned task or available to collaborate. The device can also be configured to play ring and message tones on incoming calls and/or instant messages.

The Blynclight Plus automatically displays user presence/status by synchronizing with the users UC application (Skype for Business, Cisco Jabber, RingCentral etc.). As the users presence/status changes within the UC application so does the color of the Blynclight with the light color displayed matching that of users current presence/status.

By displaying user availability in this manner, a user can increase their productivity by limiting interruptions caused by colleagues in their work environment.

Features and benefits

Lighting

- Display Surface
Cube design with matte finish allows the light to effectively display user visual alerts yet remain unobtrusive.
- Full RGB LEDs
5 LEDs using the RGB color model allows any color to be displayed on the device.
- Brightness Control
10 step brightness control allows the light to be set in any environment without being distracting.

Audio

- Built-in speaker
Positioned within the device to ensure sound is clear and distributed in a uniform manner within its environment.
- Ring and Message tones
Designed for the corporate environment, the device provides 10 different tones that can be configured to play on incoming call, instant message and/or status change.
- Volume Control
10 step volume control ensures the device can be set to an audible range without being distracting.

Connection

- Micro-USB
The device includes a 5ft black USB cable which plugs into a female Micro-USB port on the device. The device has been designed to allow the USB cable to be interchangeable to allow for environments that require a longer or shorter cable.

Deployment

- Enterprise Admin Console
Management application that allows an administrator to develop a Blynclight configuration to be pushed out to all machines and prevent client machines from configuring their own devices.
- Group Policy
Blynclight Plus configurations can be deployed across an organisation using Group Policy to ensure all devices are configured in a consistent manner.

Warranty and support

- 12-month replacement warranty
Devices will be replaced if it has failed or found to have any malfunction within a 12 month period.
- Electronic and telephone support
Online support ticket system with telephone and remote control assistance for escalations.
- Software releases
The Blynlight application is continually being improved with regular software updates based on customer feedback.
- Developer forum
Join the Embrava Developer Forum to gain access to a host of applications built by our developer community geared towards the Blynlight.

Supported Platforms

Operating Systems

- Microsoft Windows - XP, Vista, 7, 8 (32-bit and 64-bit)
- Apple Mac OSX - 10.6, 10.7, 10.8, 10.9
 - Requires Lync Server 2013 for synchronized presence display.
 - Presence display only - does not support incoming call/instant message alerts.

Applications

- Skype for Business/Microsoft Lync 2013, 2010
- Skype for Windows Desktop v7
- Cisco Jabber for Windows 11, 10, 9
- RingCentral
- Cisco Finesse
- CounterPath Bria 4
- Google+ Hangouts (on-call alerts only)
- Lync Attendant 2010
 - Requires Lync Server 2013 for synchronized presence display.
 - Presence display only - does not support incoming call/instant message alerts.

Specifications

Physical Characteristics	
Dimensions	1.77(w) x 1.77(d) x 2.36(h) in. / 45(w) x 45(d) x 60(h) mm.
Weight	2.18oz / 62g
Interface	
Adapter	Micro-B receptacle
Protocol	Supports USB 1.1, 2.0, 3.0
Cable	Black 5ft Micro-B plug
Lighting	
LED	5 x RGB LED
Color	Supports full RGB color model
Brightness	10 step brightness adjustment
Sound	
Speaker	8Ω,Φ20x3.5mm
Tones	10 ring/message tones
Volume	10 step volume adjustment
Mounting	
	0.78(w) x 0.78(h) in. / 20(w) x 20(h) mm 3M mount adhesive.
Packaging	
	<ul style="list-style-type: none"> • Brown card box • 2.9(w) x 2.0(d) x 3.7(h) in. / 73(w) x 51(d) x 94(h) mm • 4.7oz / 132g • Includes Blynlight, USB cable, mount adhesive, instruction slip
Environment	
Operating temperature	14° to 122° F / -10° to 50° C
Heat emitted	< 32° F / < 0.1° C
Electrical Characteristics	
Maximum voltage	5 V
Maximum current	300 mA
Power rating	1.5 W
Compliance	
	<ul style="list-style-type: none"> • CE • RoHS

© Copyright 2017 Embrava Inc.

Skype, Lync and Windows are either registered trademarks of Microsoft Corporation in the United States and/or other countries.

Mac and OS X are trademarks of Apple Inc., registered in the U.S. and other countries.

Cisco Jabber is a trademark of Cisco Systems Inc., registered in the U.S. and other countries.

RingCentral is a trademark of RingCentral Inc., registered in the U.S. and other countries.

Google is a trademark of Google Inc., registered in the U.S. and other countries.

CounterPath is a trademark of CounterPath Corporation, registered in the U.S. and other countries.